

## SECTION 12484 – FLOOR MATS AND FRAMES

### PART 1 - GENERAL

#### 1.01 DESCRIPTION

- A. The extent of floor mat installation (surface and recessed) is shown on Walgreens Fixture Plan.
- B. Floor mats will be furnished and installed by Walgreens. This section describes the quality of related work to be provided by the General Contractor.
- C. The General Contractor shall be responsible for installing the vestibule recess and floor drain in stores designated to receive an entry vestibule.

#### 1.02 QUALITY ASSURANCE

- A. Flame/Smoke Resistance Standards: Walgreens supplied materials comply with the following:
  - 1. Pill Test (entrance grid): For flammability, complies with ASTM D 2859, <1inch.
- B. Surfaces designated to receive floor mats shall be constructed in accordance with the manufacturer's instructions.

### PART II - PRODUCTS

#### 2.01 FLOOR MAT (provided by Walgreens)

- A. Manufacturer: Space-Links®, Inc.
- B. Entrance Grid: Recessed or surface mounted, with aluminum frame
  - 1. Style: Design Links Entryway Flooring System™.
  - 2. Type: Entrance grid.
  - 3. Size: 4-ft x 4-ft.
  - 4. Thickness: 15/32 inch.
  - 5. Color: Gray.
- C. Carpet Tile Manufacturer: Heckmondwike Carpet Company.
  - 1. Style: Dreadnought.
  - 2. Color: Anthracite.
  - 3. Adhesive: TacFast backing.
  - 4. Edging: Black rubber.

### PART III - EXECUTION

3.01 INSTALLATION (by Walgreens)

3.02 PRE-INSTALLATION REQUIREMENTS (by General Contractor)

- A. Surface mounted floor mats shall be installed on top of resilient flooring.
- B. At recessed installations, install floor drain and prepare recess in accordance with Walgreens Criteria details. Slope recess to drain located at center of recessed area.
- C. Clear away debris and scrape up cementitious deposits from surfaces to receive floor mats.
- D. Protect installed floor mats from damage during remaining construction.
- E. Ensure that floor mat will be undamaged at time of acceptance by Walgreens.

END OF SECTION