

SECTION 09900
PAINTING

PART 1 – GENERAL

1.1 DESCRIPTION

A. Scope of Work:

1. The Contractor shall furnish all materials, labor equipment, and incidentals required to provide a protective coating system for the surfaces listed herein and not otherwise excluded. All surfaces described, whether new or existing, shall be included within the scope of this section.
2. The work includes painting finishing of interior and exterior exposed items and surfaces such as walls, floors, miscellaneous metal, doors, frames, construction signs, posts, fittings, valves, equipment, and all other work obviously required to be painted unless otherwise specified herein or on the Drawings. The omission of minor items in the schedule of work shall not relieve the Contractor of his obligation to include such items where they come within the general intent of the Specifications as stated herein. The following major items of the Project shall be painted:

1.3 SUBMITTALS

A. Submittal shall include manufacturer's data and samples as indicated below and shall be prepared and submitted in time to provide adequate review by the Engineer. Submittals shall be submitted in accordance with Section 01340.

B. Samples – Painting:

1. Paint colors will be specified on the drawings. Compliance with all other requirements is the exclusive responsibility of the Contractor.
2. Samples of each finish and color shall be submitted to the Owner for approval prior to beginning any work.

PAINTING
09900-2

PRODUCTS

- A. Building paints. Manufacturer: Glidden
Contact ICI Deluxe paints for paint mixes 407-855-1512
- a. Exterior Stucco Walls – “Tusk Tusk” Semi Gloss
 - b. Exterior Stucco Wall below tile band @ “V” cap, -“Ivory Beige” Semi Gloss
 - c. Exterior Stucco trim and bands and Doors – “ABC Tan” Oil Base
 - d. Interior walls – “English Cottage” Semi-Gloss
 - e. Interior columns, doors, door jams/ misc. metals. - “Crème Brule” Oil base. / Wood Base- Crème Brule- Semi Gloss
 - f. Stain for all wood trim. “Fruitwood” by Minwax.
 - g. Varnish for all wood trim. 2 coats of Clear Satin Urethane.
 - h. Block sealer as manufactured by Glidden.
 - i. Sign post and boxes. Devguard, gloss enamel, “Architectural Brown”
 - j. Masonite backing and standards- “Hawthorne Green”-Semi Gloss

Painting notes, all drywall and exterior finishes such as wood, stucco shall be primed, prior to painting minimum of 2 coats shall be applied. Primer shall be an approved Glidden Product.

Wood trim: shall have one heavy coat stain and two coats of urethane. All cedar to be left in its natural state.

Masonite must be sanded prior to painting.

END OF SECTION
PAINTING
09900-2