

SECTION 09720

SPECIAL WALL SURFACES

PART 1 GENERAL

- 1.01 DIVISION OF RESPONSIBILITIES TERMINOLOGY: **NOT USED**
- 1.02 SUMMARY: Provide Special Wall Surfaces where shown on the drawings, as specified in this Section, and as needed for a complete and proper installation
- 1.03 SUBMITTAL: No submittal is required for the work of this Section IF provided per the construction documents. Any Request for Product Substitution must be submitted per Section 01340-Submittals.
- 1.04 WARRANTY: The Contractor shall provide the manufacturers' standard product warranties in the Building Maintenance Manuals per Section 01700-Contract Closeout.

PART 2 PRODUCTS

2.01 FRP/ PRE-FINISHED INTERIOR WALL PANELS AND TRIM MOLDINGS:

- A. FRP panels and trim moldings shall be purchased by the Contractor from this PETCO Inventory Agreement Vendor, and installed by the Contractor:

CRANE COMPOSITES
Contact: Wade Warford (e-mail wwarford@cranecomposites.com)
2017 N. Pacey Road, Phoenix AZ 85037
Tel. 425-260-3495
Website: www.cranecomposites.com

No product substitutions are permitted.

- B. Drawing Key Symbol "WF-01": The Contractor shall provide Glasbord-P", Color #66 Silver, pebble embossed, Class C fire rated PIF per ASTM A-84. No product substitutions are permitted.
1. WF-01 Vinyl Trim Moldings: Provide Inside and Outside Corner, Exposed Edge and Panel Joint Trims in Color #66 Silver
- C. Adhesive: Provide adhesive manufactured for FRP work, equal to Titebond Solvent-Free Fast Grab FRP Adhesive.

2.02 DOGGIE DAY CAMP WAINSCOT WALL COVERING: **NOT USED**

PART 3 EXECUTION

- 3.01 SURFACE CONDITIONS: The Contractor shall examine the areas and conditions under which work of this Section will be provided, shall correct conditions detrimental to the timely and proper completion of the work, and shall NOT proceed until unsatisfactory conditions are corrected. Commencement of installation work constitutes acceptance of the substrate surface.
- 3.02 INSTALLATION: Install all Special Wall Surfaces according to the manufacturers' standard written instructions, using adhesives, fasteners and trim moldings manufactured for the intended purpose, and per the manufacturer's recommendations. Exposed mechanical fasteners are NOT permitted.

END OF SECTION

